

**Listing of the Claims**

1. (canceled)
- 5 2. (Previously Presented) The apparatus for mapping image shapes for a display device of claim 8, wherein the integrating rod has a fully open entrance.
3. (Previously Presented) The apparatus for mapping image shapes for a display device of claim 8, wherein the integrating rod has a partially open entrance.
- 10 4. (original) The apparatus for mapping image shapes for a display device of claim 3, wherein the integrating rod has an exit and the partially open entrance has a reflective surface facing the exit.
- 15 5. (original) The apparatus for mapping image shapes for a display device of claim 3, wherein the integrating rod has an exit and the partially open entrance has a partially reflective surface facing the exit.
- 20 6. (Previously Presented) The apparatus for mapping image shapes for a display device of claim 8, wherein the means for selecting includes an image processor.
- 25 7. (Previously Presented) The apparatus for mapping image shapes for a display device of claim 8, wherein the means for selecting is configured to automatically select an image aspect ratio or shape without intervention by a user of the display device.

8. (Previously Presented) An apparatus for mapping image shapes for a display device, comprising:

an integrating rod;

means for selecting an image aspect ratio or shape; and

5 means for reshaping light exiting from the integrating rod depending upon the image aspect ratio or shape;

wherein the means for selecting is configured to select an image aspect ratio or shape in response to an input provided by a user of the display device.

10 9. (Previously Presented) An apparatus for mapping image shapes for a display device, comprising:

an integrating rod;

means for selecting an image aspect ratio or shape; and

15 means for reshaping light exiting from the integrating rod depending upon the image aspect ratio or shape;

wherein the means for reshaping includes a member with a plurality of differently shaped apertures formed therethrough.

20 10. (original) The apparatus for mapping image shapes for a display device of claim 9, wherein the member includes a light reflecting surface facing an exit of the integrating rod.

25 11. (original) The apparatus for mapping image shapes for a display device of claim 9, wherein the member includes a light absorbing surface facing an exit of the integrating rod.

30 12. (original) The apparatus for mapping image shapes for a display device of claim 9, wherein the means for reshaping includes means for positioning the member adjacent an exit of the integrating rod depending upon the image aspect ratio or shape.

13. (original) The apparatus for mapping image shapes for a display device of claim 9, wherein the apertures are positioned adjacent a periphery of the member.

14. (original) The apparatus for mapping image shapes for a display device of claim 13, wherein the periphery of the member is generally circular in shape.

5

15. (Previously Presented) An apparatus for mapping image shapes for a display device, comprising:

an integrating rod;

means for selecting an image aspect ratio or shape; and

10 means for reshaping light exiting from the integrating rod depending upon the image aspect ratio or shape;

wherein the means for reshaping includes a plurality of members and means for positioning the members adjacent an exit of the integrating rod depending upon the image aspect ratio or shape.

15

16. (original) The apparatus for mapping image shapes for a display device of claim 15, wherein the means for positioning the members is configured to provide a variable aperture adjacent the exit of the integrating rod depending upon the image aspect ratio or shape.

20

17. (original) The apparatus for mapping image shapes for a display device of claim 15, wherein the members include light reflecting surfaces facing an exit of the integrating rod.

25

18. (original) The apparatus for mapping image shapes for a display device of claim 15, wherein the members include light absorbing surfaces facing an exit of the integrating rod.

19. (Previously Presented) An apparatus for mapping image shapes for a display device, comprising:

an integrating rod;

means for selecting an image aspect ratio or shape; and

5 means for reshaping light exiting from the integrating rod depending upon the image aspect ratio or shape;

wherein the means for reshaping includes an anamorphic lens selected and positioned adjacent an exit of the integrating rod depending upon the image aspect ratio or shape.

10

20-21. (canceled)

22. (Previously Presented) The display device of claim 33, wherein the integrating rod has a fully open entrance.

15

23. (Previously Presented) A display device, comprising:

a light source;

a light modulator;

a projection lens adjacent the light modulator;

20 an integrating rod adjacent the light source;

a variable exit aperture operatively positioned between the integrating rod and the light modulator, the variable exit aperture being configured for mapping one of a plurality of different image aspect ratios or shapes onto the light modulator; and

25 means for selecting one of the plurality of different image aspect ratios or shapes;

wherein the integrating rod has a partially open entrance.

24. (original) The display device of claim 23, wherein the integrating rod has an exit and the partially open entrance has a reflective surface facing the exit.

30

25. (original) The display device of claim 23, wherein the integrating rod has an exit and the partially open entrance has a partially reflective surface facing the exit.

26. (Previously Presented) The display device of claim 33, wherein the variable exit aperture is provided by one or more members.

27. (Previously Presented) A display device, comprising:  
5 a light source;  
a light modulator;  
a projection lens adjacent the light modulator;  
an integrating rod adjacent the light source;  
a variable exit aperture operatively positioned between the integrating rod  
10 and the light modulator, the variable exit aperture being configured for mapping one of a plurality of different image aspect ratios or shapes onto the light modulator; and  
means for selecting one of the plurality of different image aspect ratios or shapes;  
wherein the variable exit aperture is provided by one or more members which  
15 include a light reflecting surface facing an exit of the integrating rod.

28. (Previously Presented) A display device, comprising:  
a light source;  
a light modulator;  
20 a projection lens adjacent the light modulator;  
an integrating rod adjacent the light source;  
a variable exit aperture operatively positioned between the integrating rod and the light modulator, the variable exit aperture being configured for mapping one of a plurality of different image aspect ratios or shapes onto the light modulator; and  
25 means for selecting one of the plurality of different image aspect ratios or shapes;  
wherein the variable exit aperture is provided by one or more members which include a light absorbing surface facing an exit of the integrating rod.

29. (Previously Presented) A display device, comprising:  
a light source;  
a light modulator;  
a projection lens adjacent the light modulator;  
5 an integrating rod adjacent the light source;  
a variable exit aperture operatively positioned between the integrating rod  
and the light modulator, the variable exit aperture being configured for mapping one  
of a plurality of different image aspect ratios or shapes onto the light modulator; and  
means for selecting one of the plurality of different image aspect ratios or  
10 shapes;  
wherein the variable exit aperture is provided by one or more members and  
includes means for positioning the one or more members adjacent an exit of the  
integrating rod depending upon a selected image aspect ratio or shape.

15 30. (Previously Presented) A display device, comprising:  
a light source;  
a light modulator;  
a projection lens adjacent the light modulator;  
an integrating rod adjacent the light source;  
20 a variable exit aperture operatively positioned between the integrating rod  
and the light modulator, the variable exit aperture being configured for mapping one  
of a plurality of different image aspect ratios or shapes onto the light modulator; and  
means for selecting one of the plurality of different image aspect ratios or  
shapes;  
25 wherein the variable exit aperture is provided by an anamorphic lens selected  
and positioned adjacent an exit of the integrating rod depending upon a selected  
image aspect ratio or shape.

31. (Previously Presented) The display device of claim 33, wherein the  
30 means for selecting includes an image processor.

32. (Previously Presented) The display device of claim 33, wherein the  
means for selecting is configured to automatically select an image aspect ratio or  
shape without intervention by a user of the display device.

33. (Previously Presented) A display device, comprising:  
a light source;  
a light modulator;  
5 a projection lens adjacent the light modulator;  
an integrating rod adjacent the light source;  
a variable exit aperture operatively positioned between the integrating rod  
and the light modulator, the variable exit aperture being configured for mapping one  
of a plurality of different image aspect ratios or shapes onto the light modulator; and  
10 means for selecting one of the plurality of different image aspect ratios or  
shapes;  
wherein the means for selecting is configured to select an image aspect ratio  
or shape in response to an input provided by a user of the display device.

15 34. (original) A method of mapping images for a display device with an  
integrating rod, comprising:  
identifying an aspect ratio or shape for an image to be projected by the  
display device; and  
positioning an object with a plurality of differently shaped and/or sized  
20 apertures adjacent an exit of the integrating rod depending upon the aspect ratio or  
shape to selectively obstruct portions of the exit of the integrating rod.

35. (original) A method of mapping images for a display device with an  
integrating rod, comprising:  
25 identifying an aspect ratio or shape for an image to be projected by the  
display device; and  
positioning a plurality of objects adjacent an exit of the integrating rod  
depending upon the aspect ratio or shape to selectively obstruct portions of the exit  
of the integrating rod.

30

Claims 36-38 (Cancelled).